



FiberTite® Roofing Systems LEED® Product Submittal Data

PRODUCT REFERENCE: FTR-Value_A

Energy & Atmosphere– Minimum Energy Performance: Prerequisite 2	Polyisocyanurate roof insulation is thermally efficient and can contribute toward exceeding ASHRAE 90.1-1999 as well as local energy codes
--	---

Energy & Atmosphere– Optimize Energy Performance: Credit 1	Polyisocyanurate roof insulation offers the highest thermal resistance per inch of roof insulation material and can contribute to achieving economically / optimized energy performance
---	--

MR Credit 4.1; 4.2 – Recycled Content	Percent by Weight (%)	Post-Consumer Weight %	Pre-Consumer Weight %
Thickness (inches) : 1.0	43	24.5	18.5
1.1	40	22.8	17.2
1.2	38	21.7	16.3
1.3	36	20.5	15.5
1.4	35	20.0	15.0
1.5	33	18.8	14.2
1.6	32	18.2	13.8
1.7	30	17.1	12.9
1.8	29	16.5	12.5
1.9	28	16.0	12.0
2.0	27	15.4	11.6

MR Credit 5.1; 5.2 – Regional Materials	Location
Primary Manufacturing – City, State, Zip Code:	Camp Hill, Pennsylvania 17011
	LaGrange, Georgia 3024
	Diboll, Texas 75941
	East Moline, Illinois 61244
	Northglenn, Colorado 80233
	Phoenix, Arizona 85043
Extraction of Raw Materials – City / State	N/A

*FiberTite is a Registered Trademark of Seaman Corporation
LEED is a Registered Trademark of the U.S. Green Building Council*

