



FiberTite® Roofing Systems LEED® Product Submittal Data

PRODUCT REFERENCE: FTR-Value_H

Energy & Atmosphere– Minimum Energy Performance: Prerequisite 2	Polyisocyanurate roof insulation is thermally efficient and can contribute toward exceeding ASHRAE 90.1-1999 as well as local energy codes
--	---

Energy & Atmosphere– Optimize Energy Performance: Credit 1	Polyisocyanurate roof insulation offers the highest thermal resistance per inch of roof insulation material and can contribute to achieving economically / optimized energy performance
---	--

MR Credit 4.1; 4.2 – Recycled Content	Percent by Weight (%)	Post-Consumer Weight %	Pre-Consumer Weight %
Thickness (inches) : 1.0	37.8	27.8	10.0
1.1	36.2	26.2	10.0
1.2	34.5	24.6	9.9
1.3	33.2	23.3	9.9
1.4	31.9	22.1	9.8
1.5	30.8	21.0	9.8
1.6	29.7	20.0	9.7
1.7	28.8	19.1	9.7
1.8	28.0	18.3	9.7
1.9	27.2	17.5	9.7
2.0	26.5	16.9	9.6

MR Credit 5.1; 5.2 – Regional Materials	Location
Primary Manufacturing – City, State, Zip Code:	Kinston, New York 12401
	Terrell, Texas 75160
	Chicago, Illinois 60131
	Lake City, Florida 32025
	Toole, Utah 84074
	Smithfield, Pennsylvania 15478
Extraction of Raw Materials – City / State	N/A

*FiberTite is a Registered Trademark of Seaman Corporation
LEED is a Registered Trademark of the U.S. Green Building Council*

