



## FTR Termination Bar

### Product Data

FTR Termination Bar is designed and intended for attaching and sealing FiberTite membrane and flashing terminations.

#### DESCRIPTION

FTR Termination Bar is designed and intended for use with FiberTite Roofing Systems (FTR). FTR Termination Bar is made of corrosion-resistant extruded 6063 T5 aluminum with a mill type finish.

Bars are pre-punched with slotted holes measuring 0.28 in x 0.38 in (0.66 cm x 0.97 cm) at 7.8 in (2.0 cm) intervals. Each FTR Termination bar measures 10 ft (3m) in length. There are no minimum quantities required for packaging.

Fasteners with metal, neoprene backed sealing washers are to be used when bars are going to be exposed to the weather. Seaman Corporation offers a variety of fasteners for use with FTR Termination Bars as substrates dictate.

#### APPLICATION

Seaman Corporation's FTR Termination Bar is designed for mechanical attachment to either provide linear restraint at flashing transitions or compression seals at flashing termination points. Consult the most current versions of Seaman Corporation's Guide Specifications for the Installation of FiberTite Roofing Systems and Installation Details for installation requirements, cautions and parameters.

#### PHYSICAL PROPERTIES

<i>T-Bar with Lip</i>	
Thickness	0.125 in (0.32 cm)
Width	1.0 in (2.5 cm)
Lip Width	0.25 in (0.64 cm)
Lip Angle	45°
<i>Flat Bar</i>	
Thickness	0.125 in (0.32 cm)
Width	1.0 in (2.5 cm)



For more information on FiberTite Systems and accessories please call:  
Seaman Corporation (800) 927-8578  
International (330) 262-1111  
[www.fibertite.com](http://www.fibertite.com)

**INTELLIGENT**  
ROOFING SOLUTIONS

FiberTite® is a registered trademark of Seaman Corporation.

